

# SERIES 37



80 Shore A



-5°C to +40°C



40 - 125mm



30 - 80kg

## Grey rubber small wheel and castors

- Grey non-marking rubber tyre on a black nylon centre including threadguards and ANB
- Light duty applications
- Zinc plated pressed steel castors housings
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22881:2004



### Available Bore Types



Plain  
Bore

### Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

### Uses

Suitable for use on different types of trolleys within the furniture and institutional sector. They can also be used on fragile floors and in presence of small obstacles. Example of recommended applications: shop display units and windows, low carrying capacity tool trolleys, supermarket trolleys.

### Industries



Clean Room  
Laboratories




Food  
Industry




Medical

### Floor Suitability


Suitable on tiles and resin-cement; not recommended on abrasive, unpaved floors or in presence of processing residues. They do not damage floors and are also suitable in the presence of small obstacles.



Tile



Cement-Resin



Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: [sales@aut.co.uk](mailto:sales@aut.co.uk)

# SERIES 37 CONTINUED



80 Shore A



-5°C to +40°C



40 - 125mm










30 - 80kg

## WHEELS





















Plain Bore

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (kg)	 (code)
40	18	8	21	30	0.03	371100
50	20	8	22	35	0.06	371101
60	24	8	28	50	0.10	371102
75	24	8	28	55	0.14	371203
80	24	8	28	55	0.17	371103
100	24	8	28	60	0.22	371104
125	30	10	35	80	0.46	371105



















## TOP PLATE CASTORS

								 3 km/h	 (kg)	SWIVEL	 (kg)	FIXED	 (kg)	SWIVEL & BRAKE	
	40	18	59	42x42	30x30	5	24	78	30	0.12	374100	0.11	375100	0.15	378100
	50	18	66	55x55	40x40	6	24	76	35	0.20	374101	0.20	375101	0.24	378101
	60	24	83	60x60	45x45	6	21	83	50	0.28	374102	0.26	375102	0.40	378102
	75	24	101	60x60	45x45	6	25	91	55	0.40	374303	0.31	375303	0.48	378303
	80	24	104	60x60	45x45	6	25	91	55	0.43	374103	0.34	375103	0.50	378103
	100	24	121	60x60	45x45	6	32	95	55	0.48	374104	0.40	375104	0.57	378104
	125	30	152	77x67	55x45	8	40	115	80	0.87	374105	0.80	375105	0.97	378105



## BOLT HOLE CASTORS

							 3 km/h	 (kg)	BOLT HOLE	 (kg)	BOLT HOLE & BRAKE	
	40	18	59	35	10	24	78	30	0.11	373100	0.14	377100
	50	18	66	35	10	24	76	35	0.16	373101	0.19	377101
	60	24	83	41	12	21	83	50	0.25	373102	0.32	377102
	75	24	101	41	12	25	91	55	0.31	373303	0.40	377303
	80	24	104	41	12	25	91	55	0.34	373103	0.43	377103
	100	24	121	41	12	32	91	55	0.40	373104	0.49	377104
	125	30	149	52	12	40	115	80	0.76	373105	0.87	377105



80 Shore A



-5°C to +40°C



40 - 125mm



30 - 80kg

## BOLT HOLE CASTORS WITH THREADED STEM



											<b>BOLT HOLE</b>		<b>BOLT HOLE &amp; BRAKE</b>
	40	18	59	15	M8	35	24	78	30	0.13	<b>376100</b>	0.18	<b>379100</b>
	50	20	66	15	M8	35	24	76	35	0.18	<b>376101</b>	0.21	<b>379101</b>
	60	24	83	25	M12	41	21	83	50	0.29	<b>376102</b>	0.36	<b>379102</b>
	75	24	101	25	M12	41	25	91	55	0.36	<b>376303</b>	0.43	<b>379303</b>
	80	24	104	25	M12	41	25	91	55	0.39	<b>376103</b>	0.46	<b>379103</b>
	100	24	121	25	M12	41	32	95	55	0.44	<b>376104</b>	0.53	<b>379104</b>
	125	30	149	25	M12	35	40	115	80	0.79	<b>376105</b>	0.89	<b>379105</b>

## TWIN WHEEL TOP PLATE CASTORS



											<b>SWIVEL</b>		<b>SWIVEL &amp; BRAKE</b>
	50	18+18	70	60x60	45x45	6	30	82	60	0.35	<b>374201</b>	0.40	<b>378201</b>
	75	24+24	100	60x60	45x45	6	33	95	80	0.64	<b>374203</b>	0.72	<b>378203</b>

## TWIN WHEEL BOLT HOLE CASTORS WITH THREADED STEM



											<b>BOLT HOLE</b>		<b>BOLT HOLE &amp; BRAKE</b>
	50	18+18	70	42	M10	15	30	82	60	0.30	<b>376201</b>	0.37	<b>379201</b>
	75	24+24	100	52	M12	25	33	95	80	0.50	<b>376203</b>	0.68	<b>379203</b>

For technical help and advice contact

**T: 01457 837772 E: sales@aut.co.uk**