

SERIES 65HT



95 Shore A



-20°C to +80°C



100 - 250mm



350 - 1000kg

Wheels in thick 'TR' polyurethane with aluminium centre

- Thick rounded profile gives excellent rolling resistance and elasticity. Highly resistant to wear and tear
- Medium-heavy duty loads
- Reduces fatigue in pushing, excellent ability to overcome obstacles. High performance in part manual-mechanical and mechanical handling, even at high speed (12km/h with correct bracket)
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Ball Bearing



Ball Bearing Facility

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Designed to improve trolleys' handling under heavy loads on uneven surfaces. The thick tread guarantees: excellent ability to overcome obstacles, reduced fatigue when pushing the trolley, excellent performance in presence of mechanical handling or mixed manual-mechanical handling, excellent performance over time, even at high speeds (up to 12km/h).

Industries



Airport/
Aerospace




Automotive




Towing/
Mechanical
Handling

Floor Suitability


Suitable for all types of industrial floors, except unpaved; it easily overcomes obstacles.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 65HT CONTINUED



95 Shore A



-20°C to +80°C



100 - 250mm



350 - 1000kg

WHEELS



Ball Bearing



Ball Bearing Facility

(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(daN)	(daN)	(daN)	(kg)	(code)	(kg)	(code)
100	40	15	40	32	9	500	270	350	0.46	652302	0.38	654302
125	40	20	50	47	14	650	280	450	0.76	652303	0.41	654303
160	50	20	58	47	14.5	900	320	700	1.18	652304	0.95	654304
180	50	20	58	47	14	950	335	750	1.44	652305	1.21	654305
200	50	20	58	47	14	1000	350	800	1.76	652306	1.52	654306
250	50	20	55	52	15	1200	380	1000	2.40	652308	2.10	654308

MEDIUM-HEAVY DUTY CASTORS - P






											SWIVEL		FIXED		SWIVEL & BRAKE
100	40	138	100x85	80x60	9	46	123	350	1.33	655603	0.83	655412	1.50	655502	

HEAVY DUTY CASTORS - P



											SWIVEL		FIXED		SWIVEL & BRAKE
125	40	170	140x110	105x80	11	70	126	450	2.3	655303	1.63	655403	2.83	655503	
160	50	205	140x110	105x80	11	70	126	700	3.53	655310	2.04	655414	4.10	655504	
180	50	228	140x110	105x80	11	70	126	750	3.78	655305	2.36	655415	4.35	655505	
200	50	250	140x110	105x80	11	70	126	750	4.22	655316	2.76	655416	4.82	655506	
250	50	298	140x110	105x80	11	66	126	750	4.84	655318	3.74	655418	5.54	655508	

OPTIONS AVAILABLE TO ORDER



SERIES 65HT CONTINUED



95 Shore A



-20°C to +80°C



100 - 250mm



350 - 1000kg

HEAVY DUTY TOWING CASTORS - PT



											SWIVEL		FIXED		SWIVEL & BRAKE
	160	50	205	140x110	105x80	11	70	126	700	3.34	655344	2.04	655414	3.97	655544
	180	50	228	140x110	105x80	11	70	126	750	3.71	655335	2.36	655415	4.35	655535
	200	50	250	140x110	105x80	11	70	126	800	4.36	655336	2.76	655416	4.89	655536

ELECTRO WELDED CASTORS - EE MHD






											SWIVEL		FIXED		SWIVEL & BRAKE
	100	40	170	135x110	105x80	11	51	157	350	3.36	655602	2.38	655702	4.24	655802
	125	40	182	135x110	105x80	11	51	157	450	3.68	655603	2.70	655703	4.56	655803
	160	50	215	135x110	105x80	11	60	157	700	4.18	655614	3.19	655714	5.06	655814
	180	50	242	135x110	105x80	11	70	157	750	4.56	655605	3.58	655705	5.45	655808
	200	50	252	135x110	105x80	11	70	157	800	4.88	655606	3.90	655706	6.22	655806

ELECTRO WELDED SPRUNG-LOADED CASTORS EES MHD



											SWIVEL		FIXED		SWIVEL & BRAKE
	160	50	248	135x110	105x80	11	100	240	700	7.07	655004	5.82	657104	8.13	654904
	200	50	268	135x110	105x80	11	100	265	800	7.67	655006	6.42	657106	8.78	654906
	250	50	316	135x110	105x80	11	110	315	1000	8.75	655008	7.54	657108	9.99	654908

OPTIONS AVAILABLE TO ORDER



For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk