

SERIES 75



95 Shore A



-20°C to +80°C



80 - 85mm



350 - 1000kg

'TR' polyurethane rollers with steel centre

- Brown 'TR' cast polyurethane tyre
- Option of labyrinth seal to prevent entry of dust into ball bearing that can restrict rotation of roller. Ensures longer life
- Manual handling applications
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Ball Bearing

Environments of Use


- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses


Excellent for use on electric pallet trucks, also in case of heavy loads and high speed handling (up to 16km/h). Their excellent values of rolling resistance make the manual handling of heavy loads easier. The model with electro-welded brackets allows handling heavy loads while maintaining a low centre of gravity. It is a common solution to move set design in the show business sector.

Floor Suitability


Suitable for tiles and cement-resin. Not suitable if voluminous obstacles are present.



Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

SERIES 75 CONTINUED



93 Shore A



-20°C to +80°C















80 - 85mm



650 - 1000kg















TOP PLATE CASTORS

											SWIVEL		SWIVEL & BRAKE
	35	27	53	60x60	45x45	6	17	100	70	0.25	757300	0.27	757400
	50	40	71.5	60x60	45x45	6	25.5	150	83	0.57	757301	0.63	757401



BOLT HOLE CASTORS

											BOLT HOLE		BOLT HOLE & BRAKE
	35	27	53	60x60	45x45	6	17	100	70	0.21	757500	0.40	757600
	50	40	71.5	60x60	45x45	6	25.5	150	83	0.56	757501	0.61	757601

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk