

SERIES 79



75 Shore A



-20° C to +70° C



82 - 85mm



580 - 650kg

'TR Roll' elastic polyurethane pallet truck rollers with steel centre

- Excellent rolling resistance and elasticity features, highly resistant to wear
- Heavy duty loads
- Manual handling applications
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Ball Bearing



Ball Bearing Facility

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Excellent for use on electric pallet trucks, also in case of heavy loads and high speed handling (up to 12km/h). Guarantees silent running and vibration damping and are suitable also on uneven surfaces and in presence of obstacles. Excellent values of rolling resistance to make manual handling of heavy loads easier.


Industries




Pallet Trucks

Floor Suitability


Suitable for all types of industrial floors, even outdoors. Facilitates the overcoming of obstacles. Does not damage the floors.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 79 CONTINUED



75 Shore A



-20°C to +70°C



82 - 85mm



580 - 650kg














LOAD ROLLERS



Ball Bearing



Ball Bearing Facility

 (mm)	 (mm)	 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (daN)	 (daN)	 (kg)	 (code)	 (kg)	 (code)
80	90	20	90	47	14	750	490	580	1.25	792105	1.06	794105
82	60	20	60	47	14	500	400	400	0.87	792121	0.67	794121
82	70	20	70	47	14	550	450	450	0.98	792122	0.79	794122
82	90	20	90	47	14	750	580	580	1.21	792125	1.03	794125
82	100	20	100	47	14	850	620	650	1.34	792127	1.15	794127
85	70	20	70	47	14	550	450	450	1.04	792132	0.84	794132
85	80	20	80	47	16	600	520	520	1.16	792133	0.96	794133
85	90	20	90	47	14	750	580	580	1.28	792135	1.08	794135
85	100	20	100	47	14	850	650	650	1.40	792137	1.20	794137

OPTIONS AVAILABLE TO ORDER

