

SERIES 82MH



80 Shore A



-20°C to +60°C



80 - 250mm



65 - 300kg

Puncture proof polyurethane cellular wheels, with plastic centres

- Black plastic single and twin wheel
- Light duty applications
- Pressed steel zinc - chromatised
- Swivel castors have double ball race
- Wheel axle with screw or riveted



Available Bore Types



Roller Bearing

Environments of Use


- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses


Suitable for use with light and medium-duty loads, on any type of flooring, also for mixed indoor and outdoor use. Also suitable on sandy base.

Floor Suitability


It is functional on all type of floors and especially on uneven floors and soft floor surfaces such as grass, as well as on floor with obstacles and with chips.




Tile




Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 82MH CONTINUED



80 Shore A



-20°C to +60°C



80 - 250mm









65 - 300kg

WHEELS











Roller Bearing

TREAD PATTERN	 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
Ribbed	260	80	20	75	120	82MH1028
Ribbed	260	80	25	75	120	82MH1038
X Country	260	80	20	75	120	82MH1048
X Country	260	80	25	75	120	82MH1058



SWIVEL & FIXED CASTORS

	 260	 80	 305	 115x100	 65/75x75x90	 11	 4 km/h 120	SWIVEL	FIXED
	260	80	305	115x100	65/75x75x90	11	120	82MH1008	82MH1018
	260	80	305	115x100	65/75x75x90	11	120	82MH1208	82MH1308
	260	80+80	320	115x100	65/75x75x90	11	200	82MA1008	-