

SERIES 82



85 Shore A



-20°C to +70°C



80 - 200mm



70 - 225kg

Pneumatic (air filled) tyres on plastic wheel centres

- Pneumatic 4 ply tyre (rib or cross country tyre profile) on a black polypropylene centre
- Standard duty loads
- Zinc plated pressed steel castor housing
- Manual handling applications
- Tested in accordance with ISO 22878:2004
- Manufactured in accordance with ISO 22883:2004



Available Bore Types



Plain Bore



Roller Bearing

Environments of Use


- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses


Suitable for use with light and medium-duty loads, on any type of flooring, also for mixed indoor and outdoor use. Also suitable on sandy base.

Floor Suitability


It is functional on all type of floors and especially on uneven floors and soft floor surfaces such as grass, as well as on floor with obstacles and with chips.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES 82 CONTINUED



85 Shore A



-20° C to +70° C



80 - 200mm



70 - 225kg

RIBBED TYRE



Plain Bore



Roller Bearing

(mm)	(mm)	(mm)	(mm)	4 km/h (daN)	(kg)	(code)	(kg)	(code)
260	85	20	74	150	0.91	821601	1.03	823601
260	85	25	74	150	0.90	821602	1.00	823602

CROSS COUNTRY TYRE



Plain Bore



Roller Bearing

(mm)	(mm)	(mm)	(mm)	4 km/h (daN)	(kg)	(code)	(kg)	(code)
260	85	20	74	150	0.96	822601	1.08	824601
260	85	25	74	150	0.95	822602	1.05	824602

RIB TYRED STANDARD DUTY CASTORS - NL



								4 km/h (daN)	(kg)	SWIVEL	(kg)	FIXED
								150	2.93	825601	4.33	826601
								150	0.69	535001	0.49	535701

CROSS COUNTRY STANDARD DUTY CASTORS - NL



								4 km/h (daN)	(kg)	SWIVEL	(kg)	FIXED
								150	2.89	825602	4.38	826602
								150	2.98	825702	4.48	826702