

SERIES A



85 Shore A



0°C to +40°C



50 - 125mm



27 - 60kg

Grey tyred apparatus wheels and castors

- Grey non-marking tyre
- Light duty loads
- Pressed steel castor housing
- Threadguards as standard



Available Bore Types



Plain
Bore

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Suitable for use on different types of trolleys within the furniture and institutional sector. They can also be used on fragile floors and in presence of small obstacles. Example of recommended applications: shop display units and windows, low carrying capacity tool trolleys, supermarket trolleys.

Industries




Food Industry




Furniture

Floor Suitability


Suitable on tiles and resin-cement; not recommended on abrasive, unpaved floors or in presence of processing residues. They do not damage floors and are also suitable in the presence of small obstacles.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

SERIES A CONTINUED



85 Shore A



0°C to +40°C



50 - 125mm



27 - 60kg

TOP PLATE LIGHT DUTY CASTORS



								SWIVEL	SWIVEL & BRAKE
	50	16	70	50x50	36x36	12x6	27	A050P2Z04	A050P4Z04
	75	21	101	65x65	49x49	12x6	45	A075P2Z04	A075P4Z04
	100	26	132	75x75	55x55	15x8	55	A100P2Z04	A100P4Z04
	125	27	158	75x75	55x55	15x8	60	A125P2Z04	A125P4Z04

BOLT HOLE LIGHT DUTY CASTORS



						BOLT HOLE	BOLT HOLE & BRAKE
	50	16	70	10.5	27	A050P5Z04	A050P6Z04
	75	21	101	10.5	45	A075P5Z04	A075P6Z04
	100	26	132	12.9	55	A100P5Z04	A100P6Z04
	125	27	158	12.9	60	A125P5Z04	A125P6Z04

SWIVEL WITH STEM LIGHT DUTY CASTORS



							BOLT HOLE	BOLT HOLE & BRAKE	
	100	27	44	22	132	12.9	70	22MF1402	22MF1412

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk