

SERIES SN



70 Shore D



-20°C to +80°C



100 - 200mm



160 - 200kg

Nylon centre sandwich wheels and medium duty castors

- Grey nylon wheel with red rubber damping centre for noise reduction
- Pressed steel, zinc plated castor body
- Ball bearing has plastic threadguards
- Ideal for handling trolleys



Available Bore Types



Roller Bearing



Ball Bearing

Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses

Intended mainly for static uses, for medium-heavy capacities. The excellent rolling resistance ensures that minimum effort is needed in handling, but only on smooth floors.


Industries




Food Industry

Floor Suitability


Suitable for tiles and cement-resin. Not recommended on unpaved floors or in the presence of processing residues. They facilitate overcoming small obstacles along the path. They do not mark or damage fragile floors.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES SN CONTINUED



70 Shore D



-20°C to +80°C



100 - 200mm



160 - 200kg

WHEELS



Roller Bearing



Ball Bearing

(mm)	(mm)	(mm)	(mm)	(daN)	(code)	(code)
100	36	12	40	160	S100R1031	S100B1031
125	36	15	50	200	S125R1031	S125B1031

CASTORS



											SWIVEL	FIXED	SWIVEL & BRAKE	
											160	S100R2Z31	S100R3Z31	S100R4Z31
	100	36	12	40	125	105x80	80/77x60	9	40	200	S125R2Z31	S125R3Z31	S125R4Z31	
											160	S100B2Z31	S100B3Z31	S100B4Z31
	100	36	12	40	125	105x80	80/77x60	9	40	200	S125B2Z31	S125B3Z31	S125B4Z31	

OPTIONS AVAILABLE TO ORDER

