

# SERIES T



95 Shore A



-20°C to +60°C



100 - 125mm



250 - 300kg

## Aluminium centre wheel with brown polyurethane tyre

- Ball bearing centre
- Without threadguards
- Ideal for trolleys and pallet trucks



### Available Bore Types



Ball Bearing

### Environments of Use

- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

### Uses

Suitable for applications with medium/heavy-duty loads, also with mechanical handling, with speed up to 6km/h. The excellent rolling resistance allows an easy handling of heavy loads even with wheels of small diameter.

### Industries




Airport/  
Aerospace




Cranes &  
Gantries

### Floor Suitability


Suitable for tiles and cement-resin. Not suitable if large obstacles are present.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

# SERIES T CONTINUED



95 Shore A



-20°C to +60°C



100 - 125mm









250 - 300kg

## WHEELS













Ball  
Bearing

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
100	40	12	40	250	T100B1051
125	40	15	50	300	T125B1051



## TOP PLATE CASTORS

									 (daN)	SWIVEL	FIXED	SWIVEL & BRAKE
100	40	12	40	128	105x80	80/77x60	9	40	250	T100B2Z51	T100B3Z51	T100B4Z51
100	40	12	40	128	135x110	105x84/76	11	40	250	T100B2Z52	T100B3Z52	T100B4Z52
125	40	15	50	155	105x80	80/77x60	9	40	300	T125B2Z51	T125B3Z51	T125B4Z51
125	40	15	50	155	135x110	105x84/76	11	40	300	T125B2Z52	T125B3Z52	T125B4Z52