

SERIES TH



92 Shore A



-20°C to +80°C



100 - 125mm



250 - 300kg

Black finish theatre castors with polyurethane wheels

- Heavy duty theatre castors
- Black polyurethane tyre on aluminium centre
- Black powder coated castor housings
- Smooth running quiet tyres
- Centre of wheel can be black



Available Bore Types



Ball Bearing

Environments of use


- Weak Acids
- Strong Acids
- Water
- Alcohol
- Weak Bases
- Strong Bases
- Hydrocarbons
- Solvents

Uses


Intended mainly for static uses, for medium-heavy capacities. The excellent rolling resistance ensures that minimum effort is needed in handling, but only on smooth floors.

Floor Suitability


Suitable for tiles and cement-resin. Not recommended on unpaved floors or in the presence of processing residues. They facilitate overcoming small obstacles along the path. They do not mark or damage fragile floors.




Tile



Cement-Resin




Asphalt




With Chips



With Obstacles



Not Paved



Expanded Metal

For technical help and advice contact

T: 01457 837772 E: sales@aut.co.uk

SERIES TH CONTINUED



92 Shore A



-20°C to +80°C



100 - 125mm









250 -3000kg

WHEELS












Ball Bearing

 (mm)	 (mm)	 (mm)	 (mm)	 (daN)	 (code)
100	8	40	40	250	TH100B1021
125	10	50	40	300	TH125B1021

CASTORS



								 (kg)	SWIVEL	FIXED
100	40	128	135x110	105x80	11	50	250	TH100B2Z21	TH100B3Z21	
125	40	155	135x110	105x80	11	50	300	TH125B2Z21	TH125B3Z21	

OPTIONS AVAILABLE TO ORDER

Black centre wheel
available on request